

射出裝置選項 INJECTION UNIT OPTION		單位 UNIT	A	B	C	D	E	F	G	H
射出裝置 INJECTION UNIT	螺桿直徑 Screw diameter	mm	Ø18 Ø22 Ø25	Ø22 Ø25 Ø30	Ø25 Ø30 Ø35	Ø30 Ø35 Ø40	Ø35 Ø40 Ø45	Ø40 Ø45 Ø50	Ø45 Ø50 Ø55	Ø50 Ø55 Ø60
	理論射出容量 Theoretical injection volume	cm ³	25.5 38 49	45 58 84	68 98 134	113 154 201	173 226 286	276 349 430	350 432 522	471 570 678
	射出重量 Injection Capacity (PS)	g	23 35 45	41 52 76	62 89 122	103 140 183	157 205 260	251 317 391	332 410 496	447 541 644
	射出壓力 Injection pressure	kg/cm ²	2850 1910 1480	2342 1814 1259	2710 1890 1388	2481 1823 1395	2194 1680 1327	2102 1661 1345	2862 2318 1916	2713 2242 1884
	射出速率 Injection rate	cm ³ /s	40.2 60 77.4	46.8 61.2 88.8	62.4 90 122.4	78.8 107.5 140	116.3 151.3 192.5	143.1 175.5 213.3	164.7 207.9 256.5	198.5 240.3 286.2
	可塑化能力 Plasticizing capacity (PS)	kg/h	16 25 30	23 28 38	27 39 55	38 48 59	45 55 69	53 67 83	66 102 135	82 131 167
	螺桿轉速 Screw rotation speed	rpm	10 - 375	10 - 300	10 - 240	10 - 210	10 - 210	10 - 185	10 - 180	10 - 180
	電熱容量 Heating capacity	kW	3	3.5	5.1	6.9	7.5	8.1	11	13
	需求馬力 Required driving power	hp (kW)	10 (7.5)	10 (7.5)	15 (11.2)	20 (15)	25 (18.7)	30 (22.5)	40 (30)	50 (37.5)

項目 ITEM		UNIT	CSM-120T		CSM-150T		CSM-200T		CSM-250T		CSM-300T		CSM-430T		CSM-550T	
射出裝置選項 INJECTION UNIT OPTION		序號 SERIES NO.	I	II	I	II	I	II	I	II	I	II	I	II	I	II
			A, B	A, B	A, B, C	A, B, C	B, C, D	B, C, D	B, C, D, E	B, C, D, E	C, D, E, F	C, D, E, F	D, E, F, G	D, E, F, G	E, F, G, H	E, F, G, H
開模裝置 CLAMPING UNIT	鎖模力 Clamping force	ton	120 (60 x 2)		150 (75 x 2)		200 (100 x 2)		250 (125 x 2)		300 (150 x 2)		430 (215 x 2)		550 (275 x 2)	
	最小模厚 Minimum mold height	mm	180		200		220		220		260		280		350	
	開模行程 Opening stroke	mm	460		580		700		780		850		950		1050	
	最大開距 Maximum daylight	mm	640		780		920		1000		1100		1230		1400	
	柱內間距 Distance between tie bars (H x V)	mm	400 x 400		460 x 460		520 x 520		560 x 560		650 x 650		750 x 750		850 x 850	
	模板尺寸 Platen size (H x V)	mm	590 x 590		690 x 690		770 x 770		840 x 840		970 x 970		1090 x 1090		1240 x 1240	
	轉盤直徑 Rotary table diameter	mm	Ø530		Ø610		Ø700		Ø740		Ø840		Ø980		Ø1120	
	頂針行程 Ejector stroke	mm	120		150		150		180		180		200		200	
	頂出力 Ejector force	ton	4.9		4.9		5.8		7.7		7.7		12.5		12.5	
其他 OTHERS	電動馬力 Electric power	hp (kW)	25 (18.7)		30 (22.5)		40 (30)		50 (37.5)		60 (45)		80 (60)		100 (75)	
	油箱容量 Oil tank capacity	l	290		400		540		640		820		930		1140	
	機械尺寸 Machine dimensions (L x W x H)	m	4.4 x 1.2 x 1.9		5.0 x 1.3 x 2.0		5.5 x 1.4 x 2.1		5.8 x 1.4 x 2.3		6.3 x 1.6 x 2.4		7.1 x 1.7 x 2.6		7.8 x 1.9 x 2.8	
	機械重量 Machine weight	ton	5.7		7.8		9.4		12.2		14.5		18.8		25	