

| 型號 MODEL | | 單位 UNIT | SM-50T-LSR |
|------------------------|---|--------------------|------------|
| 射出裝置 INJECTION UNIT | 螺桿直徑 Screw diameter | mm | Ø30 |
| | 理論射出容量 Theoretical injection volume | cm ³ | 84 |
| | 射出重量 Injection Capacity (PS) | g | 76 |
| | 射出壓力 Injection pressure | kg/cm ² | 1701 |
| | 射出速率 Injection rate | cm ³ /s | 82.7 |
| | 模具電熱容量 Mold heating capacity | Kw | 4 x 3 |
| | 螺桿轉速 Screw rotation speed | rpm | 10 - 265 |
| 開模裝置 CLAMPING UNIT | 鎖模力 Clamping force | ton | 50 |
| | 最小模厚 Minimum mold height | mm | 280 |
| | 開模行程 Opening stroke | mm | 350 |
| | 最大開距 Maximum daylight | mm | 630 |
| | 柱內間距 Distance between tie bars (H x V) | mm | 320 x 320 |
| | 模板尺寸 Platen size (H x V) | mm | 455 x 455 |
| | 頂針行程 Ejector stroke | mm | 100 |
| | 頂出力 Ejector force | ton | 3.4 |

為配合設計的改進及更新，以上規格如有更改，恕不另行通知。

Due to continuous development of our products, specifications are subject to change without prior notice.

本公司亦接受特殊規格之訂製，歡迎垂詢。

Machine can be custom made upon request. Please call for further details.